

## REQUEST FOR PROPOSAL 2026-07

# Replacement of Kitchen Flooring at the CCDC

**Sealed Proposals will be accepted until Wednesday, September 10<sup>th</sup>, 2025 at 12:00 P.M to Abi Reid at the Administration Department in the Cherokee County Office Building, 110 Railroad Ave, 2<sup>nd</sup> Floor, Gaffney, South Carolina 29340.** Complete specifications and instructions are attached herewith.

Proposal documents may be obtained from Maj. Stephen at the Cherokee County Department of Corrections, by email at [sanderson@cherokeecountysheriff.net](mailto:sanderson@cherokeecountysheriff.net). Proposals shall be submitted on the form furnished and shall be submitted in a sealed envelope identifying the company name, the RFP title, the RFP number, and the RFP due date on the face of the envelope.

## Replacement of the Kitchen Flooring at the CCDC

(Cherokee County Department of Corrections)

**THERE WILL BE A MANDATORY PREBID MEETING ON AUGUST 26<sup>th</sup>, 2025 AT 10:00AM AT THE CHEROKEE COUNTY DETENTION CENTER LOCATED AT 315 E DR. LM ROSEMOND LN, SC 29340**

### SUMMARY OF WORK

New flooring must be Industrial Kitchen Grade:

Seamless epoxy or equivalent is preferred. Must be highly durable, low maintenance and long lasting. All surfaces to receive resinous flooring are to be mechanically abraded/

grinded. Etching and/or bead-blasting should not be used. Strength and Durability

Abrasion and Chemical Resistant Low Maintenance and Low Odor High Moisture Tolerance

High Traffic and Non-Slip Surface

### SUMMARY OF WORK

**The current tile flooring may be removed or covered**

New flooring should be replaced with seamless resinous flooring.

All Kitchen equipment that is touching the floor will need to be moved and stored until the project is completed. The equipment will need to be placed back in the original positions at the end of the project.

### Materials

Materials are to meet all applicable codes, regulations, and

industry standards.

Poly-Crete SLB is a 3/16" seamless, 100% Solids, cement-urethane, self-leveling, concrete resurfacing system with a natural quartz aggregate broadcast providing a slip resistant, gloss finish.

## **Labor**

New resinous epoxy coated flooring systems shall be highly durable, low maintenance and long lasting. Resinous flooring shall be installed in identified kitchen area. All surfaces to receive resinous flooring are to be mechanically abraded/ grinded. Etching and/or bead-blasting shall not be used.

## **RESINOUS FLOORING**

High Strength and Durability

Abrasion and Chemical Resistant

Low Maintenance and Low Odor

High Moisture Tolerance

High Traffic and Non-Slip Surface

Provide minimum 4" turned up resinous epoxy coated base edge.